

# Hammer Drill Driver LXT

## DHP453RFE



### Product Description

18V LXT • 42 Nm • 0 - 1 300 min<sup>-1</sup>

**Combi drill with hammer action for demanding amateur builders**

For screwdriving and drilling with or without hammer action, two power settings. Max. torque of 42 / 27 Nm. Suitable for light professional use or demanding amateur use. Includes 2 x 3,0 Ah batteries and a charger in a case.

### Product Features

- ⊙ The rubber coating on the handle ensures a firm working grip
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating

### Barcode

88381661249

### Product Specifications

Vibration Level (3 axes), Drilling	≤ 2,5 m/s <sup>2</sup>
Torque setting	16
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	36 mm
Vibration Level (3 axes), Impact Drilling	10,0 m/s <sup>2</sup>
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Tool weight with battery (EPTA)	1,7 - 2,0 kg
Battery Voltage	18 V
Sound Pressure Level	83 dB(A)
Product Dimensions (L x W x H):	239 x 79 x 227 mm
Max. fastening torque Hard/Soft	42 / 27 Nm
Impacts per Minute (IPM)	0 - 6000 / 19500 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	94 dB(A)
Voltage LXT	1
Product net weight (new)	1,4 kg
System	LXT 18V/36V
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Driving Shank	1/2"-20UNF "
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Screwing and Drilling
Drill Chuck Capacity	1,5-13 mm
Electronic brake	1

<b>Max. Drilling Diameter in Concrete</b>	13 mm
<b>Max. Drilling Diameter in Masonry</b>	13 mm
<b>No load speed</b>	0 - 400 / 1300 min <sup>-1</sup>

#### Standard Equipment

- ⊙ 1pc DC18RC Fast Charger
- ⊙ 2pcs BL1830B (3.0Ah) 18V LXT Battery
- ⊙ Carry Case

#### More info

<https://makita.ae/product/hammer-drill-driver-lxt-dhp453rfe/>