Angle Grinder 9557HNG

Thakita



Product Description

840 W • 115 mm • 11 000 min⁻¹
Compact tool with slide switch for cutting and grinding
A small angle grinder with 840 W motor and 115 mm wheel.
Labyrinth channel construction protects the armature and the field coil from impurities in the cooling air. Equipped with a slide switch.

Product Features

- Reliable machined gears provide twice or more longer service life
- Ocmpact design with small diameter barrel and lightweight for added comfort
- In Protective zig-zag varnish seals the armature from dust and debris for longer tool life

 Labyrinth construction seals and protects the drive gear and bearings from contamination for longer tool life

- Slide switch with lock-on for continuous use
- Push button spindle lock for operator convenience
- Double insulated

Barcode

88381636254

| D | | 1.01 | 1.1 |
|----------|--------|---------|-------|
| Produ | uct Sn | ecifica | tions |
| | acc op | 001100 | |

| Bore Size (Arbor Diameter) | 22,23 mm | |
|--|---------------------------------|--|
| Bore Size (Arbor Diameter) | 22,23 mm | |
| Vibration Level, Surface Grinding | 7,5 m/s² | |
| Grinding Disc Diameter | 115 mm | |
| Power Supply Cord | 2,5 m | |
| Vibration Uncertainty (K Factor), Disc Sanding | 1,5 m/s ² | |
| Product Dimensions (L x W x H): | 271 x 130 x 106 mm | |
| Max Output Power | 1000 W | |
| Vibration Uncertainty (K Factor), Surface Grinding | 1,5 m/s² | |
| Sound Pressure Level | 89 dB(A) | |
| Vibration Level, Disc Sanding | ≤ 2,5 m/s ² | |
| Noise Uncertainty (K Factor) | 3 dB(A) | |
| Weight Without Cable (EPTA) | 1,7 - 2,2 kg | |
| Continuous Input Power | 840 W | |
| Tool Category | Grinding, Sanding and Polishing | |
| No load speed | 11000 min ⁻¹ | |
| Spindle Thread | M14 | |
| Sound Power Level (L _{wa}) | 97 dB(A) | |

https://makita.ae/product/angle-grinder-9557hng/